

**WPD720/WPD220**

**POLE DISPLAY**

**MANUAL**

# WPD720/WPD220 POLE DISPLAY

## INDEX

INTRODUCTION .....	3
1. FEATURES .....	4
2. GENERAL SPECIFICATIONS .....	5
3. INTERFACE SPECIFICATIONS.....	7
4. SYSTEM COMMAND DETAILS .....	8
5. COMMAND.....	10
6. CHARACTER SET.....	22

# **WPD720/WPD220 POLE DISPLAY**

## **INTRODUCTION**

Thank you for choosing the WPD720/WPD220 VFD Customer Pole Display. The WPD720/WPD220 provides both reliability and performance in a professional looking design. In this guide, you will find connection and configuration information to help you connect the display to your computer. If you are a programmer, you will find interface command details to allow you to exploit the advanced features of the display.

The WPD720/WPD220 customer pole display uses a vacuum fluorescent display (VFD) tube presenting bright and easy to read characters. Because of the VFD technology the display is viewable from a wide angle. Users will appreciate not having to remain in a fixed viewing position to see the display, they will be free to move forward in line and still keep the display readable. The WPD720/WPD220 customer pole display has 2 pole sections giving you the choice of 4 different display heights. The display can be rotated up to 270°. The head of the display can tilt by up to 35°. The combination of these features gives you flexibility to tailor the display position to your unique application.

The WPD720/WPD220 customer pole display uses an easy to connect USB connection with a wide range of available communication speeds from 300 to 38,400bps. The USB connection creates a Virtual COM port to provide communication to the pole display.

# WPD720/WPD220 POLE DISPLAY

## 1. FEATURES

- 20 columns x 2 lines
- Display panel is adjustable both by tilting vertically and rotating horizontally.
- Configuration of baud rate, command emulation mode, and user defined font is selectable by window based support software or by using external setting box.
- Command emulation modes include CD5220II, Epson, ADM787, ADM788, Aedex, Emax and Ultimate.
- Reverse characters (black characters on blue green background) can be specified using the Epson command set.
- USB Virtual COM serial interface, with communication speeds from 300 to 38400 BPS.

# WPD720/WPD220 POLE DISPLAY

## 2. GENERAL SPECIFICATIONS

Display method	Vacuum fluorescent display		
Display color	Blue green		
Number of characters	40 characters ( 20 columns x 2 lines)		
Brightness	700 cd/m2		
Character type	96 alphanumeric 13 kinds of international character set and 1 user-define character set		
Character font	5 x 7 dot matrix, comma, decimal point		
Character size	9.2mm x 5.25mm		
Character pitch	8.3mm		
Power supply	5VDC USB		
Power consumption	4.5W		
MTBF(power on time)	25000 hours		
Dimensions	230(W)x100(H)x42(D)mm		
Viewing angle	±30 degrees		
Rotation angle	Maximum 270 degrees		
Weight	0.9 Kg		
Environmental Condition	Operating	Temperature	5 - 45℃
		Humidity	Less then 95%
	Storage	Temperature	-5 - 55℃
		Humidity	Less then 95%
Safety	FCC class B    CE		

Table 1-2

## WPD720/WPD220 POLE DISPLAY

ITEM	WPD220		
Display method	Vacuum fluorescent display		
Display color	Blue green		
Number of characters	40 characters(20 columns × 2lines)		
Brightness	700 cd/m2		
Character type	96 alphanumeric 13 kinds of international character set and 1 user-define set		
Character font	5 ×7dot matrix		
Character size	3.5mm×5.0mm		
Character pitch	2mm		
Power supply	5VDC		
Power consumption	5W		
MTBF(power on time)	25000hours		
Dimensions	170(W)×70(H)×45(D)mm		
Viewing angle	± 30 degrees		
Rotation angle	Maximum 270 degrees		
Weight	0.9Kg		
Environmental Conditions	Operating	Temperature	5-45℃
		Humidity	Less then 95%
	Storage	Temperature	-5-55℃
		Humidity	Less then 95%
Safety	FCC class B 、CE		

# **WPD720/WPD220 POLE DISPLAY**

## **3. INTERFACE SPECIFICATIONS**

### **3.1 USB Virtual COM Port / Serial Port Emulation**

# WPD720/WPD220 POLE DISPLAY

## 4. SYSTEM COMMAND DETAILS

### 4.1 Baud rate

**STX 05 B n ETX** /Set baud rate and keep it with EEPROM/

ASCII Format STX 05 B n ETX

Dec. Format [02][05][66] n [03]

Hex. Format [02h][05h] [42h] n [03h]  $30h \leq n \leq 37h$

Description Change the display communication baud rate. The baud rate setting can be selected from 300 to 38400. The setting function will be saved to EEPROM.

N	Baud rate
30h	9600
31h	4800
32h	2400
33h	1200
34h	600
35h	300
36h	38400
37h	19200

### 4.2 International character set

**STX 05 S n ETX** Change international character set

ASCII Format STX 05 S n ETX

Dec. Format [02][05][83] n [03]

Hex. Format [02h][05h] [53h] n [03h]  $30h \leq n \leq 3fh$

Description Change the display international character font. A total of 16 different character fonts to select from. The setting function will be saved to EEPROM.

n	International font	n	International font
30h	U.S.A	38h	JAPAN
31h	FRANCE	39h	NORWAY
32h	GERMANY	3Ah	DENMARK II
33h	U.K	3Bh	SLAVONIC
34h	DENMARK I	3Ch	RUSSIA
35h	SWEDEN	3Dh	Factory define
36h	ITALY	3Eh	Factory define
37h	SPAIN	3Fh	User define pattern

### 4.3 Command type select

**STX 05 C n ETX** Change command type

ASCII Format STX 05 C n ETX

Dec. Format [02][05][67] n [03]

Hex. Format [02h][05h] [43h] n [03h]  $30h \leq n \leq 37h$

Description This command will change the command type and initialize the display. The display emulation mode is based on CD5220II/ESC POS/ADM787/ADM788/ UTC/AEDEX/EMAX mode. The setting function will be saved to EEPROM.

n	Command type	n	Command type
30h	DSP800	34h	AEDEX
31h	ESC/POS	35h	UTC/P
32h	ADM788	36h	UTC/S
33h	ADM787	37h	CD5220



# WPD720/WPD220 POLE DISPLAY

## 4.4 Reset EEPROM

<b>STX 05 07 n ETX</b>	Reset EEPROM
ASCII Format	STX 05 07 n ETX
Dec. Format	[02][05][07][n][03]
Hex. Format	[02h][05h][07h][n][03h]
Description	This command will reset the content of EEPROM (eg. demo scroll data, user-define character, baud rate setting.) n=31h clear all EEPROM contents n=32h clear upper line data message n=33h clear lower line data message

## 4.5 Save data for demo display

<b>STX 05 L n m ETX</b>	Save demo message to EEPROM
ASCII Format	STX 05 L n m ETX
Dec. Format	[02][05][76] n m [03]
Hex. Format	[02h][05h][4Ch] n m [03h]
Description	Save demo message for upper line and bottom line n = 31h save data message for upper line n = 32h save data message for lower line m = data message; the maximum data character is under 200

## 4.6 Run Demo message

<b>STX 05 D 08 ETX</b>	Run demo message
ASCII Format	STX 05 D 08 ETX
Dec. Format	[02][05][68][08][03]
Hex. Format	[02h][05h][44h][08][03h]
Description	Run demo message for the display

## 4.7 Set Communication Option

<b>STX 05 P n ETX</b>	Set the communication parity
ASCII Format	STX 05 P n ETX
Dec. Format	[02][05][80] n [03]
Hex. Format	[02h][05h][50h] n [03h] 31h≤n≤36h
Description	Change the display communication parity. Set 7 or 8 data bit and the parity set for even, odd, or non-parity.

n	Parity
31h	N-8-1
32h	N-7-1
33h	E-8-1
34h	E-7-1
35h	O-8-1
36h	O-7-1

# WPD720/WPD220 POLE DISPLAY

## 5. COMMAND

### 5.1 Command list

#### 5.1.1 WPD720/220 STANDARD MODE

Command	Code description (hex)	Function description
ESC DC1	1B 11	overwrite mode
ESC DC2	1B 12	vertical scroll mode
ESC DC3	1B 13	horizontal scroll mode
ESC Q A .....CR	1B 51 41 [n]x20 0D	set the string display mode, write string to upper line
ESC Q B .....CR	1B 51 42 [n]x20 0D	set the string display mode, write string to lower line
ESC Q D .....CR	1B 51 44 [n]x20 0D	upper line message scroll continuously
ESC [ D	1B 5B 44	move cursor left
BS	08	move cursor left
ESC [ C	1B 5B 43	move cursor right
HT	09	move cursor right
ESC [ A	1B 5B 41	move cursor up
ESC [ B	1B 5B 42	move cursor down
LF	0A	move cursor down
ESC [ H	1B 5B 48	move cursor to home position
HOM	0B	move cursor to home position
ESC [ L	1B 5B 4C	move cursor to left-most position
CR	0D	move cursor to left-most position
ESC [ R	1B 5B 52	move cursor to right-most position
ESC [ K	1B 5B 4B	move cursor to bottom position
ESC l x y	1B 6C x y 1≤x≤20,y=1,2	move cursor to specified position
ESC @	1B 40	initialize display
ESC W s x1 x2 y	1B 57 1 x1 x2 y    1≤x1≤x2≤20 y=1,2	reset window range at horizontal scroll mode
CLR	0C	clear display screen, and clear string mode
CAN	18	clear cursor line, and clear string mode
ESC * n	1B 2A n                      1≤n≤4	brightness adjustment
ESC & s n m [a(p1..pa)]x (m-n+!)	1B 26 1 n m [a(p1..pa)]x (m-n+1) 20h<n≤m≤FFh a=1-5 , p1..p5 =row1..row5	define download characters.
ESC ?	1B 3F	delete download characters.
ESC %	1B 25	select/cancel download character set.
ESC _ n	1B 5F n                      n=0,1	set cursor ON/OFF
ESC f n	1B 66 n	select international fonts
ESC c n	1B 63 n	select fonts, ASCII code or JIS code
ESC s l	1B 73 01	store user-define character into EEPROM
ESC d l	1B 64 01	restore user-define character from EEPROM
ESC = n	1B 3D n n=1; enable printer, disable display n=2; disable printer, enable display n=3; enable printer, enable display n=4; message for customer side (NA) n=5; message for operator side (NA) default n=2	select peripheral device, display or printer: display for customer side or display for operator side

Table 6-1

#### (REMARK)

\* While using command "ESC QA" or "ESC QB", these two commands can be used with terminal printer: TP2688 or TP3688

\* While using command "ESC QA" or "ESC QB", other commands can not be used except when using command "CLR" or "CAN" to change operating mode.

\* When using command "ESC QD", the upper line message will scroll continuously until a new command is received, it will then clear the upper line and move the cursor to the upper left-end position.

# WPD720/WPD220 POLE DISPLAY

Set international font for WPD720/WPD220 (Table 6-2)

n	International font set	n	International font set
A	U.S.A.	N	NORWAY
G	GERMANY	W	SWEDEN
I	ITALY	D	DENMARK I
J	JAPAN	E	DENMARK II
U	U.K.	L	SLAVONIC
F	FRANCE	R	RUSSIA
S	SPAIN		reserved

Select code for WPD720/WPD220 (Table 6-3)

n	International code set
A	Compliance with ASCII code
J	Compliance with JIS code
R	Compliance with RUSSIA code
L	Compliance with SLAVONIC code
P	PC858
W	WPC1252

## 5.1.2 ADM787/788 command list

Command	Code description (hex)	Function description
CLR	0C	clear display
CR	0D	carriage return
SLE1	0E	clear upper line and move cursor to upper left-end position
SLE2	0F	clear bottom line and move cursor to bottom left-end position
DC0	10 n	set period to upper line, last n position $31h \leq n \leq 37h$
DC1	11 n	set line blinking, upper line n='1', bottom line n='2'
DC2	12 n	clear line blinking, upper line n='1', bottom line n='2'
SF1	1E	clear field 1 and move cursor to field 1, first position
SF2	1F	clear field 2 and move cursor to field 2, first position

Table 6-4

## 5.1.3 UTC standard mode command list

Command	Code description (hex)	Function description
BS	08	back space
HT	09	horizontal tab
LF	0A	line feed
CR	0D	carriage return
DLE	0F	display position
DC1	11	overwrite display mode
DC2	12	vertical scroll mode
DC3	13	cursor on
DC4	14	cursor off
ESC d	1B 64	change to UTC enhanced mode
US	1F	clear display

Table 6-5

## 5.1.4 UTC enhanced mode command list

Command	Code description (hex)	Function description
ESC u A ....CR	1B 75 41 [ data x 40] 0D	upper line display
ESC u B ....CR	1B 75 42 [ data x 40] 0D	bottom line display
ESC u D ....CR	1B 75 44 [ data x 40] 0D	upper line message scroll continuously
ESC u E ....CR	1B 75 45 hh ':' mm 0D h,m='0'-'9'	display time
ESC u F ....CR	1B 75 46 [ data x 40] 0D	upper line message scroll once
ESC u H ....CR	1B 75 48 n m 0D $20h \leq n, m$	change attention code
ESC u I ....CR	1B 75 49 [ data x 40] 0D	two line display
ESC RS CR	1B 0F 0D	change to UTC standard mode

Table 6-6

# WPD720/WPD220 POLE DISPLAY

## 5.1.5 AEDEX mode command list

Command	Code description (hex)	Function description
! # 1 ....CR	21 23 31 [data x 40]	upper line display
! # 2 ....CR	21 23 32 [data x 40]	bottom line display
! # 4 ....CR	21 23 34 [data x 40]	upper line message scroll continuously
! # 5 ....CR	21 23 35 hh ':' mm 0D h,m='0'-'9'	display time
! # 6 ....CR	21 23 36 [data x 40]	upper line message scroll once pass
! # 8 ....CR	21 23 38 n m 0D     20h≤n,m	change attention code
! # 9 ....CR	21 23 39 [data x 40]	two line display

Table 6-7

## 5.1.6 DSP-800 mode command list

Command	Code description (hex)	Function descriptions
EOT SOH I n ETB	04 01 49 n 17	select international character set
EOT SOH P n ETB	04 01 50 n 17     n=31h-58h	move cursor to specified position
EOT SOH C n m ETB	04 01 43 n m 17 31h≤n≤m≤58h	clear display range from <u>n</u> position to <u>m</u> position and move cursor to <u>n</u> position
EOT SOH S n ETB	04 01 53 n 17     n=31h-35h	save current view message to n layer for demo view data
EOT SOH D n m ETB	04 01 44 n m 17 n=31h-4Fh     m=31h-33h	display the saved demo message
EOT SOH A n ETB	04 01 41 n 17     n=31h-34h	brightness adjustment
EOT SOH F n ETB	04 01 46 n 17     00h≤n<FFh	blink display screen
EOT SOH & n [px5] ETB	04 01 26 n p1...p5 17,     20h≤n	define download characters
EOT SOH ? n ETB	04 01 3F n 17     20h≤n	delete download characters
EOT SOH = n ETB	04 01 3D n 17	select peripheral device select printer n='1', display n='2'
EOT SOH % ETB	04 01 25 17	initialize display
EOT SOH @ ETB	04 01 40 17	execute self-test
EOT SOH B n N ETB	04 01 42 n 4E 17     n=31h-36h	set baud rate and parity

Table 6-8

### (REMARK)

\* International font set (Table 6-9)

n	International font set
30h	U.S.A.
31h	France
32h	Germany
33h	U.K.
34h	Denmark I
35h	Sweden
36h	Italy
37h	Spain
38h	Japan
39h	Norway
3Ah	Denmark II

# WPD720/WPD220 POLE DISPLAY

## 5.1.7 EPSON ESC/POS command list

Command	Code description(hex)	Function description
HT	09	move cursor right
BS	08	move cursor left
US LF	1F 0A	move cursor up
LF	0A	move cursor down
US CR	1F 0D	move cursor to right-end position
CR	0D	move cursor to left-end position
HOM	0B	move cursor to home position
US B	1F 42	move cursor to bottom position
US \$ x y	1F 24 x y $1 \leq x \leq 20, y=1,2$	move cursor to specified position
CLR	0C	clear display screen
CAN	18	clear cursor line
US X n	1F 58 n $1 \leq n \leq 4$	brightness adjustment
US E n	1F 45 n $0 \leq n \leq 255$	blink display screen
ESC @	1B 40	initialize display
ESC t n	1B 74 n $1 \leq n \leq 15$	select character code table
ESC R n	1B 52 n $1 \leq n \leq 15$	select international character set
US r n	1F 72 n $n=0,1$	select/cancel reverse character
US MD1	1F 01	specify overwrite mode
US MD2	1F 02	specify vertical scroll mode
US MD3	1F 03	specify horizontal scroll mode
ESC & s n m [a(p1..pa)]x m-n	1B 26 1 n m [a(p1..pa)]x m-n $20h < n \leq m \leq FFh; a=1-5, p1..p5=row1..row5$	define download characters
ESC ?	1B 3F	delete download characters
ESC %	1B 25	select/cancel download character set
ESC W n s x1 y1 x2 y2	1B 57 n s x1 y1 x2 y2 $n=1-4, s=0,1, 1 \leq x1 \leq x2 \leq 20; 1 \leq y1 \leq y2 \leq 2$	reset window range
ESC = n	1B 3D n (default n=2) n=1; enable printer, disable display n=2; disable printer, enable display n=3; enable printer, enable display For WPD720D only: n=4; message for customer side n=5; message for operator side	select peripheral device
US :	1F 3A	set starting/ending position to define macro
US ^ n m	1F 5E n m, $0 \leq (n, m) \leq 255$	execute and quit macro
US @	1F 40	execute self-test
ESC s 1	1F 73 01	store defined download character to EEPROM
ESC d 1	1F 64 01	restore user-define character from EEPROM
ESC T h m	1B 54 h m, $0 \leq h \leq 23, 0 \leq m \leq 59$	display time
US . n	1F 2E n, n = a displayable character code	specify period
US , n	1F 2C n, n = a displayable character code	specify comma
US ; n	1F 3B n, n = a displayable character code	specify semicolon (period + comma )
US # n m	1F 23 n m, n = 0 or 1, $0 \leq m \leq 20$	turn annunciator ON/OFF

Table 6-10

Set international font for ESC/POS (Table 6-11)

n	International font set	n	International font set
0	U.S.A.	7	SPAIN
1	FRANCE	8	JAPAN
2	GERMANY	9	NORWAY
3	U.K.	10	DENMARK II
4	DENMARK I	11	SLAVONIC
5	SWEDEN	12	RUSSIA
6	ITALY	15	Reserved

Select code for ESC/POS (Table 6-12)

n	International font set (80H-FFH)
0	Page 0,(PC437:U.S.A.,standard Europe)
1	Page 1,(Katakana for Japan )
2	Page 2,(PC850:multilingual)
3	Page 3,(PC860:Portuguese)
4	Page 4,(PC863:Canadian-French)
5	Page 5,(PC865:Nordic)
6	Page 6,(SLAVONIC)
7	Page 7,(RUSSLA)
19	Page 8,(PC858:Euro)
16	Page 9,(WPC1252)

# WPD720/WPD220 POLE DISPLAY

## 5.2 WPD720/WPD220 standard command details

<b>ESC DC1</b>	/Overwrite mode/
ASCII Format	ESC DC1
Dec. Format	[027][017]
Hex. Format	[1Bh][11h]
Description	Change the display mode to the overwrite mode. In this mode, the cursor will move rightward and begin from the upper left-end position. When the cursor reached the end of the upper line, the cursor will move down to the bottom left-end position to continue. When the cursor reached the end of the bottom line, it will move up to the upper left-end position and overwrite the previous characters.
<b>ESC DC2</b>	/Vertical scroll mode/
ASCII Format	ESC DC2
Dec. Format	[027][018]
Hex. Format	[1Bh][12h]
Description	Change the display mode to the vertical scroll mode. In this mode, the cursor will move rightward. The cursor will begin from the upper left-end position until it reached the end of the upper line, the cursor will then move down to the bottom left-end position to continue until it reached the end of the bottom line. Then, WPD720/WPD220 will scroll the bottom line up to replace the upper line. The bottom line will be cleared, and the cursor will continue to the first position of the bottom line.
<b>ESC DC3</b>	/Horizontal scroll mode/
ASCII Format	ESC DC3
Dec. Format	[027][019]
Hex. Format	[1Bh][13h]
Description	Change the display mode to the horizontal mode. In this mode, the extend of the cursor activity is bond by predefined range, limited to the upper line. (Please refer to Set or cancel window command), where the default window is the whole upper line. Once the cursor activity reached the end of the range, the characters that comes there after will push displayed characters forward from behind.
<b>ESC Q A d1d2d3d4d5d6.....dn CR</b>	
<b>ESC Q B d1d2d3d4d5d6.....dn CR</b>	/Set the string display mode, and write string to display/
ASCII Format	ESC Q A d1d2d3d4d5d6...dn CR ESC Q B d1d2d3d4d5d6...dn CR
Dec. Format	[027][081][065] d1d2d3..dn [013] [027][081][066] d1d2d3..dn [013]
Hex. Format	[1Bh][51h][41h] d1d2d3..dn [0Dh] [1Bh][51H][42h] d1d2d3..dn [0Dh] {20h≤dn≤ffh}
Description	Set the string display mode, write to upper or lower line d1 d2 d3 . . . dn {1≤n≤20} “A” stands for the upper line, “B” stands for the lower line. The string display mode will be cancelled and back to last mode after receive CLR or CAN.
<b>ESC Q D d1d2d3d4d5d6.....dn CR</b>	/ Upper line message scroll continuously
ASCII Format	ESC Q D d1d2d3d4d5d6...dn CR
Dec. Format	[027][081][068] d1d2d3..dn [013]
Hex. Format	[1Bh][51h][44h] d1d2d3..dn [0Dh] {20h≤dn≤ffh}
Description	The message (previously defined) will scroll continuously in the horizontal direction until a new command is received.

## WPD720/WPD220 POLE DISPLAY

<b>ESC [ D</b>	/Move cursor left/
<b>BS</b>	/Move cursor left/
ASCII Format	ESC [ D
Dec. Format	[027][091][068]
Hex. Format	[1Bh][5Bh][44h]
ASCII Format	BS
Dec. Format	[008]
Hex. Format	[08h]
Description	<p>When the current cursor is at the left-end position, this command operates differently depends on the display mode.</p> <ol style="list-style-type: none"> <li>1. Overwrite mode: When the cursor reached the left-end of the lower line, it will continue to the right-end of the upper line, overwrite previous characters. When it reached the left end of the upper line, it will continue to the right-end of the lower line.</li> <li>2. Vertical scroll mode: When the cursor reached the left-end of the lower line, the lower line will scroll up and replace the previous upper line, the lower line will be cleared and the cursor will continue to the right end of the lower line.</li> <li>3. Horizontal scroll mode: The cursor will remain stationary.</li> </ol>
<b>ESC [ C</b>	/Move cursor right/
<b>HT</b>	/Move cursor right/
ASCII Format	ESC [ C
Dec. Format	[027][091][067]
Hex. Format	[1Bh][5Bh][43h]
ASCII Format	HT
Dec. Format	[009]
Hex. Format	[09h]
Description	<p>Move the cursor to the right. When the cursor reached the right-end, this command operates differently depending on the display mode.</p> <ol style="list-style-type: none"> <li>1. Overwrite mode: When the cursor reached the right-end of the lower line, it will continue to the left-end of the upper line, overwrite previous characters. When it reached the right-end of the upper line, it will continue to the right-end of the lower line.</li> <li>2. Vertical scroll mode: When the cursor reached the right-end of the lower line, the lower line will scroll up to replace the upper line, the lower line is cleared and ready to continue characters there after.</li> <li>3. Horizontal scroll mode: The cursor will remain stationary.</li> </ol>
<b>ESC [ A</b>	/Move cursor up/
ASCII Format	ESC [ A
Dec. Format	[027][091][065]
Hex. Format	[1Bh][5Bh][41h]
Description	<p>Move the cursor up one line. When the cursor is on the upper line, this command operates differently depending on the display mode.</p> <ol style="list-style-type: none"> <li>1. Overwrite mode: The cursor is moved to the same column on the lower line.</li> <li>2. Vertical scroll mode: The characters display on the upper line are scrolled to the lower line, and the upper line is cleared. The cursor will remain at the same position.</li> <li>3. Horizontal scroll mode: The cursor will remain stationary.</li> </ol>
<b>ESC [ B</b>	/Move cursor down/
<b>LF</b>	/Move cursor down/
ASCII Format	ESC [ B
Dec. Format	[027][091][066]
Hex. Format	[1Bh][5Bh][42h]
ASCII Format	LF
Dec. Format	[010]
Hex. Format	[0Ah]
Description	<p>Move the cursor down one line. When the cursor reached the lower line, this command operates differently depending on the display mode.</p> <ol style="list-style-type: none"> <li>1. Overwrite mode: The cursor is moved to the same column on the upper line.</li> <li>2. Vertical scroll mode: The characters display on the lower line are scrolled to the upper line, and the lower line is cleared. The cursor will remain at the same position.</li> <li>3. Horizontal scroll mode: The cursor will remain stationary.</li> </ol>

# WPD720/WPD220 POLE DISPLAY

<b>ESC [ H</b>	/Move cursor to home position/
<b>HOM</b>	/Move cursor to home position/
ASCII Format	ESC [ H
Dec. Format	[027][091][072]
Hex. Format	[1Bh][5Bh][48h]
ASCII Format	HOM
Dec. Format	[011]
Hex. Format	[0Bh]
Description	The cursor will move to the left-end position of the upper line
<b>ESC [ L</b>	/Move cursor to left-most position/
<b>CR</b>	/Move cursor to left-most position/
ASCII Format	ESC [ L
Dec. Format	[027][091][076]
Hex. Format	[1Bh][5Bh][4Ch]
ASCII Format	CR
Dec. Format	[013]
Hex. Format	[0Dh]
Description	The cursor will be moved to the left-end position of the current line.
<b>ESC [ R</b>	/Move cursor to right-most position/
ASCII Format	ESC [ R
Dec. Format	[027][091][082]
Hex. Format	[1Bh][5Bh][52h]
Description	The cursor will be moved to the right-end position of the current line.
<b>ESC [ K</b>	/Move cursor to bottom position/
ASCII Format	ESC [ K
Dec. Format	[027][091][075]
Hex. Format	[1Bh][5Bh][4Bh]
Description	The cursor will be moved to the right-end position on the lower line.
<b>ESC 1 x y</b>	/Move cursor to specified position/
ASCII Format	ESC 1 x y
Dec. Format	[027][108] x y { 1≤x≤20 , 1≤y≤2 }
Hex. Format	[1Bh][6Ch][x][y]
Description	The cursor will be moved to the x column on the y line.
<b>ESC @</b>	/Initialize display/
ASCII Format	ESC @
Dec. Format	[027][064]
Hex. Format	[1Bh][40h]
Description	The data in the input buffer will be cleared and reset from default.
<b>ESC W s x1x2 y</b>	/Reset the window/
ASCII Format	ESC W s x1 x2 y
Dec. Format	[027][087][000]
Hex. Format	[027][087][001] x1 x2 y { 1≤x1≤x2≤20 , 1≤y≤2 }
Hex. Format	[1Bh][57h][000]
	[1Bh][57H][01h][x1][x2][y]
Description	Reset the window on the display. When s = 0, window is cancelled (values: x1, x2, and y are not required.) When s = 1 the window will be reset (values: x1, x2, and y are required.) The x1 and x2 set the position of the left column and right column, respectively, of the window. The y sets the upper line or the lower line of the window. This function is valid within the horizontal mode.



# WPD720/WPD220 POLE DISPLAY

**CLR** /Clear display screen, and clear string mode/  
 ASCII Format CLR  
 Dec. Format [012]  
 Hex. Format [0Ch]  
 Description All the display characters will be cleared, and the string mode will be cancelled.

**CAN** /Clear current line, and cancel string mode/  
 ASCII Format CAN  
 Dec. Format [024]  
 Hex. Format [18h]  
 Description The current line is cleared, and the string mode is cancelled.

**ESC \* n** /Brightness adjustment /  
 ASCII Format ESC \* n  
 Dec. Format [027][042] n {3<=n<=4}  
 Hex. Format [1Bh][2Ah][n]  
 Description Adjust the brightness of the vacuum fluorescent display.  
 When n = 3 ,brightness = 70 %  
 When n = 4 ,brightness =100 %

**ESC \_ n** /Set cursor ON or OFF /  
 ASCII Format ESC \_ n  
 Dec. Format [027][095] n {0<=n<=1}  
 Hex. Format [1Bh][5Fh][n]  
 Description: Set cursor ON or OFF  
 When n = 0, cursor is OFF  
 When n = 1, cursor is ON

**ESC f n** /Select international font/  
 ASCII Format ESC f n  
 Dec. Format [027][102] n  
 Hex. Format [1Bh][66h][n]  
 Description Set international font

n	International font set	n	International font set
A	U.S.A.	N	NORWAY
G	GERMANY	W	SWEDEN
I	ITALY	D	DENMARK I
J	JAPAN	E	DENMARK II
U	U.K.	L	SLAVONIC
F	FRANCE	R	RUSSIA
S	SPAIN		reserved

Table 6-11

**ESC c n** /Select fonts /  
 ASCII Format ESC c n  
 Dec. Format [027][099] n  
 Hex. Format [1Bh][63h][n]  
 Description Select fonts

n	International font set	n	International
A	compliance with ASCII code	R	compliance with RUSSIA code
J	compliance with JIS code	L	compliance with SLAVONIC code

Table 6-12

## WPD720/WPD220 POLE DISPLAY

<b>ESC = n</b>	/Select peripheral device, Display or Printer/
ASCII Format	ESC = n
Dec. Format	[027][061] n {n=1,2,3}
Hex. Format	[1Bh][3Dh][n]
Description	Select peripheral device When n = 01h, enable printer, disable display When n = 02h, disable printer, enable display When n = 03h, enable printer, enable display For WPD720D only: When n = 04h, display message for customer side When n = 05h, display message for operator side /Set user-defined characters/
<b>ESC &amp; s n m</b> <b>[a(p1...pa)]</b> <b>x(m-n+1) n</b>	
ASCII Format	ESC & s n m [a(p1...pa)] x (m-n+1) s=1
Dec. Format	[027][038][001] n m [a(p1...pa)] x (m-n+1) 20h≤n≤m≤FFh
Hex. Format	[1Bh][26h][01h][n][m][a(p1...pa)] x (m-n+1) 0≤a≤5 0≤p1...pa≤255
Description	The n defines the beginning character code, and m defines the ending character code. When only one character is defined, use n = m The “a” denotes the number of dots in the horizontal direction. When a < 5, the dot pattern for “a” on the right side of the user-defined characters are padded with spaces p1... pa, the dot data is to defined the characters. This indicates the dot pattern for “a” in the horizontal direction from the left side.
<b>ESC % n</b>	/Reset user defined character set/
ASCII Format	ESC % n
Dec. Format	[027][037] n {n=0 or 1 }
Hex. Format	[1Bh][25h][n]
Description	When n=1, user-defined characters are selected. When the user-defined characters are not defined by the ESC & command, the internal character set will be displayed. When n=0, user-defined characters are cancelled and the international character set is selected.
<b>ESC ? n</b>	/Cancel user defined characters/
ASCII Format	ESC ? n
Dec. Format	[027][063] n {20h≤n≤FFh or 1 }
Hex. Format	[1Bh][3Fh][n]
Description	User-defined characters are cancelled. This command cancels the defined characters specified by n. If specified code is transmitted after the pattern is cancelled, the international character will be displayed.
<b>ESC s 1</b>	/Store the user defined character into EEPROM. (EEPROM type only )/
ASCII Format	ESC s 1
Dec. Format	[027][115] [001]
Hex. Format	[1Bh][73h][01h]
Description	This command is successful when the display is selected under command ESC=03h If EEPROM is not supported, this command is ignored.
<b>ESC d 1</b>	/Restore the user defined character from EEPROM. (EEPROM type only)/
ASCII Format	ESC d 1
Dec. Format	[027][100] [001]
Hex. Format	[1Bh][64h][01h]
Description	WPD720/WPD220 will restore user-defined characters from EEPROM, and the user-defined characters will be selected. If EEPROM is not supported, this command is ignored.

# WPD720/WPD220 POLE DISPLAY

## 6. CHARACTER SET

( 1 )Control code set

HEX	CODE	HEX	CODE
00H	NULL	10H	DLE
01H	MD1	11H	DC1
02H	MD2	12H	DC2
03H	MD3	13H	DC3
04H	MD4	14H	DC4
05H	MD5	15H	
06H	MD6	16H	
07H	MD7	17H	
08H	BS,MD8	18H	CAN
09H	HT	19H	
0AH	LF	1AH	
0BH	HOM	1BH	ESC
0CH	CLR	1CH	
0DH	CR	1DH	
0EH	SLE1	1EH	SF1
0FH	RS,SLE2	1FH	US,SF2

( 2 )U.S.A font set

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
20h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
30h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
40h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
50h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
60h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
70h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

# WPD720/WPD220 POLE DISPLAY

### ( 3 ) International character selection

( Indicate character selection by dip switch or command)

## ASCII CODE

[illegible]

# WPD720/WPD220 POLE DISPLAY

( 4 ) PC-437 Standard Europe international font set

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
80h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
90h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
A0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
B0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
C0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
E0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
F0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

( 5 ) PC-850 ( multilingual international font set)

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
80h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
90h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
A0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
B0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
C0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
E0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
F0h	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

# WPD720/WPD220 POLE DISPLAY

( 6 ) PC-860 Portuguese international font set

[illegible]

( 7 ) PC-863 Canadian French international font set

[illegible]

# WPD720/WPD220 POLE DISPLAY

( 8 ) PC-865 NORDIC (international font set)

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
80h	.0000	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
90h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
A0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
B0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
C0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
D0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
E0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
F0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.

( 9 ) SLAVONIC Font set

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
80h	.0000	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
90h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
A0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
B0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
C0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
D0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
E0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.
F0h	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.	.0.0.

# WPD720/WPD220 POLE DISPLAY

( 10 ) RUSSIA font set

[illegible]

( 11 ) Katakana font set

[illegible]



# WPD720/WPD220 POLE DISPLAY

( 12 ) PC-858

[illegible]

( 13 ) WPC1252

[illegible]